

GRP:  
450, 455, 460

**Optical Power Meter**

The smallest  
Optical Power  
Meter on the  
market



## More than an Optical Power Meter...

Greenlee's new (GRP) style Optical Power Meters combine functionality, style & advanced applications expected in more advanced optical Test & Measurement equipment and are available in calibrated wavelengths of 850nm, 1310nm, 1550nm & the new PON wavelength of 1490nm.

Referenced & Absolute optical power readings (dB & dBm) are available as standard and On-board storage of 1000 measurements for each of the 4 wavelengths is possible with GRP 455 & 460, along with the ability of up-loading the results to PC via mini USB port (GRP 460). Review of stored field measurements is possible with the Scroll function. Additionally, an audible signal can be heard on detection of a 2kHz modulated signal from one of Greenlee's associated Optical Light Sources for easy fibre identification.

Non Intrusive Live Fibre Identification is possible when used in conjunction with part LFI 110. Optical radiation from working circuits can be detected eliminating the potential to disconnect a working fibre, as well as detection of 2kHz modulated signal.

Connection to the fibre under test is made via the universal 2.5 mm adapter. Additional male or female connector adapter styles are available. The readily available CR 2 battery provides over 1000 operations for the power meter. A "LO BAT" display alerts the user to replace the battery.

## Features

- 850, 1310, 1490, 1550nm
- Referenced & Absolute optical power readings
- Store 1000 measurements per wavelength
- Download results via USB to a computer
- Audible tone alert from incoming 2kHz signal
- Accepts all connector styles
- NIST traceable measurements
- Multimode and Singlemode operation
- Long battery life
- Rugged and compact size
- Conversion to Live Fibre ID with LFI 110

## Specification

<b>dB/dBm</b>	GRP 450-02	GRP 450-03	GRP 450-04
<b>On-board storage</b>	GRP 455-02	GRP 455-03	GRP 455-04
<b>Data transfer to PC</b>	GRP 460-02	GRP 460-03	GRP 460-04
Detector type	Ge	InGaAs	Filtered InGaAs
Wavelength range	850nm to 1625nm		
Measurement range	+ 3 to - 60dBm	+ 3 to -70 dBm	+23 to -45 dBm
Resolution	0.01dB		
Absolute accuracy*	+/- 0.25dB		
Optical interface	Universal 2.5mm (Order 1.25mm or screw on adapters separately)		
Tone identification	2kHz Incoming signal, Audible Alert		
Power on	Push button ON, Auto shutoff		
Storage	Store up to 1000 measurements per wavelength GRP 455 & GRP 460		
Data transfer	Mini USB Port (1000 points/wavelength) GRP 460 ONLY		
Dimensions	6.1x.94x.75 in. (15.5x2.38x1.90cm)		
Weight	3.0 oz (8.5g)		

## Ordering Information

CAT NO.	ORDER #	DESCRIPTION	QTY.
GRP 450-02		Germanium, 0.01dB, Zero/Set Ref	1
GRP 450-03		InGaAs, 0.1dB, Zero/Set Ref	1
GRP 450-04		Filtered InGaAs, 0.01dB, Zero/Set Ref	1
GRP 455-02		Germanium, 0.01dB, Zero/Set Ref	
GRP 455-03		InGaAs, 0.01dB, Zero/Set Ref	
GRP 455-04		Filtered InGaAs, 0.01dB, Zero/Set Ref	
GRP 460-02		Germanium, 0.01dB, Zero/Set Ref	
GRP 460-03		InGaAs, 0.01dB, Zero/Set Ref	
GRP 460-04		Filtered InGaAs, 0.01dB, Zero/Set Ref	
LFI 110		Active Channel & 2kHz tone detect device	
<b>Connector Options:</b>			
AC 021		1.25mm Universal Adaptor	
AC 026		SC Adaptor for OPM	
AC 027		ST Adaptor for OPM	
AC 028		FC Adaptor for OPM	
AC 029		LC Adaptor for OPM	

## Associated Products



**Tempo Europe Limited.**  
 Brecon House, Llantarnam Park, William Brown Close, Gwmbran. NP44 3AB.  
 Tel: +44 (0) 1633 627710 Fax: +44 (0) 1633 627711  
 E-mail: tempo@klauke.textron.com • Web: www.tempo.textron.com



Distributed by:

Messkom Vertriebs GmbH,  
 Awarrenring 38,  
 D 85419 Mauern,  
 Tel.: 08764-9484-30, Fax: -33  
 Email: info@messkom.de,  
 URL: www.messkom.de